



DS-010

Pixhawk Autopilot

Bus Standard

Revision: 0.7.0

Revision date: May 18, 2023

Abstract

This document is the formal version of the Pixhawk industry standard that includes all aspects of the hardware standard required to build compatible autopilots.

Table of contents

Table of Contents	2
Document Revisions	3
Contact and Public Developer Call	4
Trademark Guideline	4
License and Disclaimer	4
Flight Management Unit Standards	5
Interface Standards	5
Common External Interfaces	6
CAN Transceivers	6
Pixhawk Autopilot Bus (PAB) and Module Standard	7
Connector X1 (PAB X1)	7
Connector X2 (PAB X2)	8
X1 Pinout	8
X2 Pinout	10
Mechanical Design	11
PCB Layout Guidelines	12
Baseboard Design Examples (FMUv5X, FMUv6X)	13
Base to FMU Connectors (X1, X2)	13
FMU Debug Connector	14
RC Inputs	15
Powerpath Selector	16
Peripheral Power Protection	17
Baseboard EEPROM and Sensor Connections	18
Ethernet Transceiver	18
GPS / Audio Interface	19

Document Revisions

Revision	Editor	Reviewer	Comments
0.1.0	Lorenz Meier	David Sidrane	Initial specification
0.2.0	Lorenz Meier	David Sidrane	Addition of FMUv6X draft
0.3.0	Lorenz Meier	David Sidrane	Split up into focused documents
0.4.0	Lorenz Meier	Andrew Smith	-
0.5.0	David Sidrane	Ramon Roche	Added I2C Pull up not
0.6.0	Dugan Yoon	David Sidrane	Updated Mechanical guidelines
0.7.0	David Sidrane	Ramon Roche	Updated PAB Pinout to RC03

Contact and Public Developer Call

This standard is being developed on a [public developer call](#).

For further questions, please contact the maintainer of the standard, lorenz@px4.io.

Trademark Guideline

Pixhawk is a registered trademark and is used to mark and protect the consistent use of this standard. The requirements for this are covered in this document: [Trademark Guideline](#)

License and Disclaimer

Copyright (c) 2020, Pixhawk Special Interests Group (SIG). All rights reserved.

Redistribution and use in products, without modification, are permitted provided that the following conditions are met:

- The trademark shall only be used for compliant products and in combination with a signed adopter agreement.
- Implementations of the standard must be compliant with the full specification.
- A royalty-free, non-exclusive license is provided to adopters with a valid adopter agreement for schematics and drawings based on the standard documentation.

THIS SPECIFICATION IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE

Flight Management Unit Standards

- FMUv1: No product name (2012, 168 MHz M4)
- FMUv2: Pixhawk 1 (2013, 168 MHz M4)
- FMUv3: Pixhawk 2 (2015, 168 MHz M4, redundant sensors)
- FMUv4: Pixracer (2015, 168 MHz M4)
- FMUv4X: Pixhawk 3 Pro (2017, 168 MHz M4, redundant sensors)
- FMUv5: Pixhawk 4 (2018, 200 MHz M7)
- FMUv5X: Pixhawk 5X (2021, 200 MHz M7,, redund. sensors)
- FMUv6U: Pixhawk 6U (2021, 400-600 MHz H7)
- FMUv6X: Pixhawk 6X (2021, 400-600 MHz H7,, redund. sensors)

Interface Standards

- **OBSOLETE:** Pixhawk connector standards v1 (2011-2015)
 - Connector: Hirose DF13
 - Pinout: Obsolete
- Pixhawk connector standards v2 (2015-)
 - Connector: JST GH
 - Pinout: [Pixhawk connector pinout](#)
- Pixhawk Autopilot Bus (PAB)
 - Connector: 100-pos Hirose DF40
 - Connector: 50-pos Hirose DF40

Common External Interfaces

This list describes the mandatory external interfaces.

Standard	FMUv5	FMUv5X	FMUv6U	FMUv6X
Stable	06/2018	06/2019	12/2020	02/2021
MCU	STM32F765	STM32F765	STM32H753	STM32H753
Clock	200 MHz	200 MHz	480 MHz	480 MHz
RAM	512 KB	512 KB	1 MB	1 MB
FLASH	2MB	2MB	2MB	2MB
PAB / SoM	x	✓	x	✓
UART (RTS/CTS)	2	3	3	3
UART (2-wire)	2	4	4	4
Debug	6-pos	10-pos	10-pos	10-pos
Ethernet	x	100-Base T	x	100-Base T
USB	2.0 12 MBit	2.0 12 MBit	2.0 12 MBit	USB-C 480 Mbit
CAN	2	2	1	3
I2C	2	3 (+NFC)	3	3 (+NFC)
Power input	analog	digital	digital	digital
PWM out	6 + 8 (IO)	8 + 8 (IO)	8	8 + 8 (IO)

CAN Transceivers


The following CAN transceivers are recommended.

- TJA1051TK/3
- MCP2562FD-H/MF

Pixhawk Autopilot Bus (PAB) and Module Standard

The usage of this bus is mandatory for all System-on-Module(SOM) designs . However, if autopilot and baseboard are integrated into one unit, this connector pair (PAB X1 and PAB X2) can be omitted. See the mechanical section for dimensions.

TIP: Leverage the Altium footprint [available in the support files folder](#)



Connector X1 (PAB X1)

The 100-pin connector is automotive grade, low-cost, vibration resilient and allows very high density assemblies.

Side	Baseboard side (bottom)	Autopilot side (top)
Part Number	Hirose DF40HC(3.0)-100DS-0.4V(58)	Hirose DF40C-100DP-0.4V(51)
Distributors	DigiKey	DigiKey
Dimensions	$A = 22.6\text{mm}$ $B = 19.6\text{mm}$	$A = 21.52\text{mm}$ $B = 19.6\text{mm}$

Connector X2 (PAB X2)


The 50-pin connector is automotive grade, low-cost, vibration resilient and allows very high density assemblies.

Side	Baseboard side (bottom)	Autopilot side (top)
------	-------------------------	----------------------


Part Number Hirose DF40HC(3.0)-50DS-0.4V(51) Hirose DF40C-50DP-0.4V(51)

Distributors [Digikey](#) [Digikey](#)

Dimensions



A = 12.6mm
B = 9.6mm



A = 11.52mm
B = 9.6mm

X1 Pinout

Mandatory main bus with the critical Pixhawk interfaces.

ODD Pins			EVEN Pins
FMU_CH8	1	2	GND (Pin 2)
FMU_CH7	3	4	BUZZER_1
FMU_CH6	5	6	GND
FMU_CH5	7	8	I2C3_SDA_BASE_MS5611_BARBED_EXTERNAL1
GND	9	10	I2C3_SCL_BASE_MS5611_BARBED_EXTERNAL1
FMU_CH4	11	12	I2C2_SDA_BASE_GPS2_MAG_LED_PM2
FMU_CH3	13	14	I2C2_SCL_BASE_GPS2_MAG_LED_PM2
FMU_CH2	15	16	I2C1_SDA_BASE_GPS1_MAG_LED_PM1
FMU_CH1	17	18	I2C1_SCL_BASE_GPS1_MAG_LED_PM1
GND	19	20	GND
FMU_SAFETY_SWITCH_IN	21	22	UART7_RTS_TELEM1
FMU_nSAFETY_SWITCH_LED_OUT	23	24	UART7_CTS_TELEM1
HW_VER_REV_DRIVE	25	26	GND
HW_VER_SENSE	27	28	UART8_TX_GPS2
V_RTC_BAT	29	30	UART8_RX_GPS2

GND	31	32	GND
VDD_3V3_SPEKTRUM_POWER_EN	33	34	USART1_RX_GPS1
VDD_5V_PERIPH_nEN	35	36	USART1_TX_GPS1
VDD_5V_PERIPH_nOC	37	38	GND
FMU_PPM_INPUT	39	40	USART2_TX_TELEM3
GND	41	42	USART2_RX_TELEM3
GND	43	44	GND
GND	45	46	USART2_RTS_TELEM3
GND	47	48	USART2_CTS_TELEM3
VDD_5V_IN	49	50	GND
VDD_5V_IN	51	52	UART5_TX_TELEM2
VDD_5V_IN	53	54	UART5_RX_TELEM2
VDD_5V_IN	55	56	GND
CAN2_TX	57	58	UART5_RTS_TELEM2
CAN2_RX	59	60	UART5_CTS_TELEM2
GND	61	62	GND
CAN1_TX	63	64	UART7_TX_TELEM1
CAN1_RX	65	66	UART7_RX_TELEM1
GND	67	68	GND
USART3_TX_DEBUG	69	70	USART6_RX_FROM_IO_RC_INPUT
USART3_RX_DEBUG	71	72	USART6_TX_TO_IO_NC
GND	73	74	GND
FMU_SWDIO	75	76	USB_D_P
FMU_SWCLK	77	78	USB_D_N
GND	79	80	VBUS_SENSE
VDD_5V_HIPOWER_nEN	81	82	GND
VDD_5V_HIPOWER_nOC	83	84	FMU_VDD_3V3
nARMED	85	86	FMU_VDD_3V3
FMU_nRST	87	88	GND
nPOWER_IN_A	89	90	ADC1_6V6
nPOWER_IN_B	91	92	ADC1_3V3
nPOWER_IN_C	93	94	GND
GND	95	96	UART4_RX
FMU_CAP1	97	98	UART4_TX
GND	99	100	GND

Note: All I2C buses are pulled up with 1.5K Resistors on the FMUM.


X2 Pinout

Advanced bus (optional) containing ethernet and external SPI port.


ODD Pins			EVEN Pins
GND (Pin 1)	1	2	ETH_MDIO
ETH_REF_CLK	3	4	ETH_MDC
GND	5	6	ETH_POWER_EN
ETH_CRS_DV	7	8	GND
GND	9	10	ETH_RX_ER
ETH_RXD0	11	12	ETH_PHY_nINT
GND	13	14	GND
ETH_RXD1	15	16	FMU_CH9
GND	17	18	FMU_CH10
ETH_TXD0	19	20	FMU_CH11
GND	21	22	FMU_CH12
ETH_TXD1	23	24	GND
GND	25	26	SPARE09
ETH_TX_EN	27	28	SPARE10
GND	29	30	SPARE11
SPI6_MISO_EXTERNAL1	31	32	SPARE12
SPI6_MOSI_EXTERNAL1	33	34	GND
SPI6_SCK_EXTERNAL1 (SWO)	35	36	SPARE14
GND	37	38	SPARE15
SPI6_nRESET_EXTERNAL1	39	40	CAN3_TX
SPI6_nCS1_EXTERNAL1	41	42	CAN3_RX
SPI6_nCS2_EXTERNAL1	43	44	PG6
SPI6_DRDY2_EXTERNAL1	45	46	GND
SPI6_DRDY1_EXTERNAL1	47	48	NFC_GPIO
SPIX_SYNC	49	50	PH11

Mechanical Design

Top view of FMUM



Bottom view of FMU SOM




For mechanical compatibility across vendors the following is advised. Locate centers of Red, Green, and Blue LEDs and SD Card connector pin 1 as shown in the Top View FMUM above.


For mechanical case compatibility across vendors the following is advised. The outer case dimensions shall be **no greater than 31.8mm x 38.8mm**. This allows a total of 1.4mm to be used for case wall thickness and clearance to FMUM pcb. It is necessary to provide heat sinking of the FMUM microprocessor. This can be accomplished by using a metal top case that thermally interfaces to the FMUM microprocessor.

PCB Layout Guidelines


- The base board should be impedance controlled with 50 ohms single ended, 90 ohms differential for USB, and 100 ohms differential for Ethernet.
- Impedance controlled signal traces should not be routed such that they cross a split in their respective reference planes. A signal crossing a plane split may cause unpredictable return path currents impacting signal quality and potentially creating EMI problems.
- Provide 3x the gap separation between adjacent ground fill copper and both USB and Ethernet differential signal traces.
- Ethernet RMII interface signals ETH_TX_EN, ETH_TXD1, ETH_TXD0, ETH_CRSDV, ETH_RXD1, ETH_RXD0 should each be kept under 6" in length with length matching to each other within 2". ETH_TXD0 is ~1" on the FMUM board and ~0.5" longer than the rest of the RMII interface signals. Therefore on the base board ETH_TXD0 should be less than 5" in length and the remainder of RMII signals should match (ETH_TXD0 - 0.5") to within 2".
- While it is possible to mount low profile components under the FMU SOM, it is recommended that some form of heatsinking provision be employed to remove heat from bottom side M7 processor U1, such as a metal housing that is thermally connected to U1. Use of such a metal housing may require a keepout area under the SOM.
- The four 2.0 mm mounting holes with 3.6 mm pads are connected to ground and are intended to provide electrical grounding to the base board through metal standoffs.
- The DF40 connectors establish a 3mm board to board spacing between the SOM and base board.
- Port protection diodes and series resistors should be placed close to the connectors they are providing protection for.
- Ethernet common mode chokes specify removing copper planes and traces from beneath the parts for best performance.




FMU Debug Connector




RC Inputs



Powerpath Selector



Peripheral Power Protection



GPS / Audio Interface

